

Amendment and Response [Under 37 C.F.R. § 1.116 - Expedited Examining Procedure]

Page 2 of 8

Serial No.: 10/790,355

Confirmation No.: 9409

Filed: 1 March 2004

For: WALK-BEHIND IMPLEMENT AND HANDLE ASSEMBLY RELEASE APPARATUS FOR
USE WITH SAME

Amendments to the Claims

- Please cancel claims 1, 3-12, 15-16, 18, 19-21, and 24-26 without prejudice.
- Please enter and consider new claims 27-30.
- This listing of claims replaces all prior versions, and listings, of claims in the above-identified application:

Listing of Claims

1. (Canceled)
2. (Canceled)
- 3.-12. (Canceled)
- 13-14. (Canceled)
- 15.-16. (Canceled)
17. (Canceled)
- 18.-21. (Canceled)
22. (Original) A walk-behind lawn mower comprising:
 - a housing operable for movement over a ground surface;
 - a handle assembly comprising a handle member, the handle member pivotally coupled to a handle retention portion of the housing and operable to be locked in at least a first operating position relative to the housing; and

Amendment and Response [Under 37 C.F.R. § 1.116 - Expedited Examining Procedure]

Page 3 of 8

Serial No.: 10/790,355

Confirmation No.: 9409

Filed: 1 March 2004

For: WALK-BEHIND IMPLEMENT AND HANDLE ASSEMBLY RELEASE APPARATUS FOR
USE WITH SAME

a handle assembly release apparatus associated with the housing, wherein the handle assembly release apparatus comprises a release member pivotable about an axis transverse to a longitudinal axis of the mower, the release member operable to selectively slide between the handle member and the handle retention portion.

23. (Currently Amended) A walk-behind lawn mower, comprising:

a housing operable for movement over a ground surface, the housing comprising a handle retention portion;

a handle assembly comprising at least one handle member, the handle assembly pivotally coupled to the handle retention portion of the housing [[,]] and operable to be selectively locked, relative to the housing, in a first operating position; and

a handle assembly release apparatus associated with the handle assembly, wherein the handle assembly release apparatus comprises a lever pivotable about an axis transverse to a longitudinal axis of the mower and operable to impart a releasing force to the at least one handle member to unlock the [[same]] handle assembly from the first operating position, and further wherein the lever comprises a contact portion operable to slide between the handle retention portion and the at least one handle member.

24.-26. (Canceled)

27. (New) A walk-behind outdoor power equipment unit comprising:

a housing operable for movement over a ground surface, the housing comprising a first handle retention portion and a second handle retention portion;

a handle assembly comprising a first handle member and a second handle member pivotally coupled, respectively, to the first handle retention portion and the second handle retention portion, wherein the handle assembly may be selectively locked, relative to the housing, in a first operating position; and

Amendment and Response [Under 37 C.F.R. § 1.116 - Expedited Examining Procedure]

Page 4 of 8

Serial No.: 10/790,355

Confirmation No.: 9409

Filed: 1 March 2004

For: WALK-BEHIND IMPLEMENT AND HANDLE ASSEMBLY RELEASE APPARATUS FOR
USE WITH SAME

a handle assembly release apparatus associated with the handle assembly, wherein the handle assembly release apparatus comprises a release member operable to both pivot about an axis transverse to a longitudinal axis of the unit, and impart a releasing force simultaneously to each of the first and second handle members to unlock the handle assembly from the first operating position, the releasing force at least partially reacted by the housing, the release member comprising contact portions operable to simultaneously slide between both the first handle retention portion and the first handle member, and between the second handle retention portion and the second handle member.

28. (New) A walk-behind outdoor power equipment unit comprising:

a housing operable for movement over a ground surface, the housing comprising a first handle retention portion and a second handle retention portion;

a handle assembly comprising a first handle member and a second handle member pivotally coupled, respectively, to the first handle retention portion and the second handle retention portion, wherein the first handle retention portion comprises a lip against which the first handle member is biased, the lip defining a first recess at a location corresponding to a first operating position of the handle assembly; and

a handle assembly release apparatus associated with the handle assembly, wherein the handle assembly release apparatus comprises a release member operable to both pivot about an axis transverse to a longitudinal axis of the unit, and impart a releasing force simultaneously to each of the first and second handle members to unlock the handle assembly from the first operating position, the releasing force at least partially reacted by the housing.

29. (New) The unit of claim 28, wherein the lip comprises a second recess at a location corresponding to a second storage position of the handle assembly.

Amendment and Response [Under 37 C.F.R. § 1.116 - Expedited Examining Procedure]

Page 5 of 8

Serial No.: 10/790,355

Confirmation No.: 9409

Filed: 1 March 2004

**For: WALK-BEHIND IMPLEMENT AND HANDLE ASSEMBLY RELEASE APPARATUS FOR
USE WITH SAME**

30. (New) A walk-behind lawn mower comprising:

a housing operable for movement over a ground surface, the housing comprising a first and a second handle retention portion;

a handle assembly comprising a first and a second handle member pivotally coupled to the first and second handle retention portions, respectively, the handle assembly operable to be selectively locked, relative to the housing, in a first operating position; and

a handle assembly release apparatus associated with the housing and operable to unlock the handle assembly from the first operating position, wherein the handle assembly release apparatus comprises a lever member operable to: simultaneously wedge between the first handle member and the first handle retention portion and between the second handle member and the second handle retention portion; and simultaneously apply a separating force between the first handle member and the first handle retention portion and between the second handle member and the second handle retention portion, and further wherein the lever member pivots about an axis that is generally horizontal and transverse to a longitudinal axis of the lawn mower.